

**Mechanical characteristics**

cables  
 interface dimensions acc. to assembly code  
 center conductor  
 outer conductor  
 mating life

**Components**

center contact  
 outer contact  
 other metal parts  
 insulator  
 crimp ferrule

**Electrical characteristics**

impedance  
 frequency  
 return loss  
 working voltage  
 voltage proof  
 insulation resistance  
 contact resistance  
 center contact  
 outer contact

**Environmental**

operating temp.  
 RoHS compliant

**Mechanische Eigenschaften**

Kabel  
 Steckgesicht nach Montageanleitung  
 Innenleiter  
 Außenleiter  
 Steckzyklen

**Bauteile**

Innenkontakt  
 Außenkontakt  
 sonstige Metallteile  
 Isolierung  
 Crimprohr

**Elektrische Eigenschaften**

Wellenwiderstand  
 Frequenz  
 Rückflusdämpfung  
 Betriebsspannung  
 Prüfspannung  
 Isolationswiderstand  
 Durchgangswiderstand  
 Innenkontakt  
 Außenkontakt

**Umgebung**

Betriebstemperatur  
 RoHS konform

cable group / Kabelgruppe G41 (0.6/2.8-4.7):  
 0.6/2.8 AF Draka, 0.6/2.8C-HM (FR-NC) Bedea,  
 1855ABelden HDTV Miniature Precision Video Cable,  
 1855NH Belden Digital Video Coax, 46899 Belden,  
 FRNC 0.6/2.8 AF (Minik.) PKI, Image 360 Argosy,  
 SDV Canford, VDM230 Gepco, VK5/0.6 FRLS 0.6/2.8 Percon

without standard / ohne Norm  
 A4737  
 crimp  
 crimp  
 ≥ 500

**Materials / Material**

ⓐ BeCu  
 brass / Messing  
 brass / Messing  
 PTFE  
 brass / Messing

**Finish / Oberfläche**


Cu1Ni2Au0,3  
 Cu2Ni5  
 Cu2Ni5  
 Cu2Ni5


75 Ω  
 0-4,5 GHz  
 TBD  
 ≤ 170 V<sub>eff</sub> / 50 Hz  
 500 V<sub>eff</sub> / 50 Hz  
 ≥ 10 GΩ

≤ 5.0 mΩ  
 ≤ 2.5 mΩ

-55°C / +155°C  
 2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]	
			gez./ drawn	06.08.2014	KL		
			gepr./ appr	25.08.2014	VM	co./approx.	
Maßstab/ scale		Benennung/ title					
5:1 (1:1)		Ultra Tiny BNC Straight Plug HD-BNC-Kabelstecker					
untst. Maße/ dim. without tolerances according to		Untert./ doc. type		Zeichnungsnr./ drawing no.			
		K		J01290A0064			
Ersatz für/ replaces							
						 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1	
a	26238	22.10.2014	MA				