

COAXIAL CONNECTOR, UHF, other Ohm, Straight cable plug (male)

11_UHF-0-4-19/033_-

Properties

- Mateable with 4 mm banana plugs
- Applicable in frequencies up to 200 MHz



Product configuration		
Interface type	Gender	Standard
UHF	plug	IEC 60169-12
Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Silver Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating
Electrical data		
Interface frequency	0.2 GHz	
Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0.1 GHz ... 0.5 GHz	20 dB	1.222
0.5 GHz ... 1 GHz	14 dB	1.499
Mechanical data		
Mating cycles	500	
Cable entry centre contact	crimped	
Cable entry outer contact	crimped	

COAXIAL CONNECTOR, UHF, other Ohm, Straight cable plug (male)

11_UHF-0-4-19/033_-

Environmental data	
Operation temperature	-55 °C ... 165°C
Ordering Information Table	
Item number	Item description
84327884	11_UHF-0-4-19/033_-E
Suitable cables	
Cable group	X34 - 4 mm / 50 Ohm X28 - 4 mm / 50 Ohm
Suitable cables	SPUMA_240 Spuma_240-RS-FR
Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3359 / Date of publication: 25.11.2023 / uncontrolled copy