

**RG179, 75 Ohm, 3 GHz, 200°C, ø2.54 mm, FEP jacket**

RG\_179\_B/U

**Properties**

- Mil standard RG cable
- Excellent RF performance for precision applications
- Suitable for use in applications up to 3 GHz
- Extended temperature range
- 75 Ohm characteristic Impedance



Construction			
Component	Material	Detail	Diameter
Centre conductor	Steel, Copper + Silver plated	Strand-07	0.31mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.55mm
Outer conductor	Copper, Silver plated	Braid, 94%	2mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	2.54 mm +/- 0.13 mm

Electrical data	
Impedance	75 Ω +/-3Ω
Operating frequency	≤ 3 GHz
Capacitance	63 pF
Velocity of signal propagation	69 %
Signal delay	4.83 ns/m
Screening effectiveness	41 dB at frequency 0.001 GHz ... 1GHz
Insulation resistance	100000000 MΩ*m
Inner conductor resistance	742 Ω/km
Operating Voltage (at sea level)	≤ 0.75 kV
Test voltage (50 Hz/1 min)	≤ 1.5 kV

Mechanical data	
Weight	approx. 14.8 g/m
Static bending radius	≥ 15 mm
Repeated bending radius	25 mm
Dynamic bending radius	< 38 mm

**RG179, 75 Ohm, 3 GHz, 200°C, ø2.54 mm, FEP jacket**

RG\_179\_B/U

Environmental data	
Operation temperature	-65 °C ... 200°C
Installation temperature	-20 °C ... 60°C
Flame propagation standard	IEC 60332-1
Fire characteristics	contains halogene

**Additional Information**

MIL reference: M17/94-RG179

**Suitable connectors**

Cable group U5

**Ordering information**

Item number	Item description	Available as assembly only
22510044	RG_179_B/U	No

**Power Matrix**Calculation: typical Attenuation [ formula:  $(a \cdot f^{0.5} + b \cdot f)$  ] and maximum Power CW [ formula:  $(p/f^{0.5})$  ]

a coefficient typical =	<b>0.73</b>	b coefficient typical =	<b>0.1014</b>
fmax =	<b>3.0</b>	P at 1 GHz =	<b>115.0</b>

Frequency GHz	Nom. attenuation (dB/m)	Nom. attenuation Max. (dB/ft)	CW power (W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.20	0.347	0.106	257
0.40	0.502	0.153	182
0.60	0.626	0.191	148
0.80	0.734	0.224	129
1.00	0.831	0.253	115
1.20	0.921	0.281	105
1.40	1.006	0.307	97
1.60	1.086	0.331	91
1.80	1.162	0.354	86
2.00	1.235	0.376	81
3.00	1.569	0.478	66

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P973 / Date of publication: 27.10.2023 / uncontrolled copy