

RG400 LSFH, 50 Ohm, 6 GHz, 105°C, ø5 mm, RADOX® jacket

ENVIROFLEX_400

Properties

- Flame retardant
- UL AWM style 3651
- CPR qualified



Construction			
Component	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Strand-19	1mm
Dielectric	SPEX (Crosslink Foam PE)		2.98mm
Outer conductor	Copper, Silver plated	Braid, 96%	3.61mm
Outer conductor	Copper, Silver plated	Braid, 94%	4.2mm
Jacket	RADOX	black/bl line	5 mm - 0.1 mm

Electrical data	
Impedance	50 Ω +/-2Ω
Operating frequency	≤ 6 GHz
Capacitance	94 pF
Velocity of signal propagation	70.3 %
Signal delay	4.74 ns/m
Screening effectiveness	70 dB at frequency 0.001 GHz ... 6GHz
Insulation resistance	10000000 MΩ*m
Inner conductor resistance	29.45 Ω/km
Operating Voltage (at sea level)	≤ 2.5 kV
Voltage Rating UL	300 V
Phase vs temperature	10000 ppm at temperature -40 ... 100°C
Phase vs bending	0.5 °/GHz
Test voltage (50 Hz/1 min)	≤ 5 kV

Mechanical data	
Weight	approx. 6 g/m
Static bending radius	≥ 10 mm
Repeated bending radius	40 mm
Dynamic bending radius	< 40 mm

RG400 LSFH, 50 Ohm, 6 GHz, 105°C, ø5 mm, RADOX® jacket

ENVIROFLEX_400

Mechanical data	
Abrasion test	MIL-T-81490 - §4.7.19 - prod. II - modified
Environmental data	
Operation temperature	-40 °C ... 105°C
Installation temperature	-20 °C ... 60°C
CPR class	Eca
Flame propagation standard	EN 60332-1-2
	UL 1581 § 1100
	IEC 60332-1
Fire characteristics	free of halogenes, acc. standard IEC 60754
Smoke test	EN 61034-2
Ageing test	MIL-C-17 § 4.8.16
Cold bend test	MIL-C-17 § 4.8.19
	IEC 60068-2-5, proc. C
Thermal stress test	IEC 61196-1 § 10.9
Toxicity test	NF X 70-100

Additional Information

Railway certificates discontinued by end of 2017. Replacement type for railway: RADOX_RF_400.

Suitable connectors

Cable group	U11
-------------	-----

Ordering information

Item number	Item description	Available as assembly only
22512280	ENVIROFLEX_400	No

Power Matrix

Calculation: typical Attenuation [formula: (a*f^0.5 + b*f)] and maximum Power CW [formula: (p/f^0.5)]

a coefficient typical =	0.402	b coefficient typical =	0.142
fmax =	6.0	P at 1 GHz =	225.0

Frequency GHz	Nom. attenuation (dB/m)	Nom. attenuation Max. (dB/ft)	CW power (W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.10	0.141	0.043	712
0.20	0.208	0.063	503
0.30	0.263	0.080	411
0.40	0.311	0.095	356
0.60	0.397	0.121	290
0.80	0.473	0.144	252
1.00	0.544	0.166	225
1.20	0.611	0.186	205
1.40	0.674	0.205	190
1.60	0.736	0.224	178
1.80	0.795	0.242	168
2.00	0.853	0.260	159
2.50	0.991	0.302	142
3.00	1.122	0.342	130
3.50	1.249	0.381	120

RG400 LSFH, 50 Ohm, 6 GHz, 105°C, ø5 mm, RADOX® jacket
ENVIROFLEX_400

Power Matrix			
4.00	1.372	0.418	112
5.00	1.609	0.490	101
6.00	1.837	0.560	92

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1117 / Date of publication: 13.11.2023 / uncontrolled copy