

HUBER+SUHNER® DATA SHEET

Low noise cable: G_02330_HT



Description

Low noise - triax - PE - 50 Ohm

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper, Tin plated	Wire	0.5 mm
Dielectric	PE (Polyethylene)		1.5 mm
Semi conductor	PVC (Polyvinyl chloride)		1.9 mm
Outer conductor	Copper	Braid, 92 %	2.4 mm
Jacket	PE (Polyethylene)		3.2 mm +/- 0.15
2 nd Screen	Copper	Braid, 92 %	3.85 mm
Outer Jacket	PVC (Polyvinyl chloride)	RAL 7011 - gr	5.3 mm +/- 0.2
Print	HUBER+SUHNER G 02330 HT 50 Ohm (PA no.)		

Electrical Data

Impedance	50 Ω
Max. operating frequency	1 GHz
Capacitance	115 pF/m
Insulation resistance	$\geq 1 \times 10^6$ MΩm
Max. operating voltage	1.5 kV _{rms} (at sea level)
Test voltage	3 kV _{rms} (50 Hz/1 min)
Max. noise level	10 mV

Mechanical Data

Weight	4.5 kg/100 m	
Min. bending radius	static repeated (for max. 50 bendings)	30 mm 60 mm

Environmental Data

Temperature range	-25 °C... + 85 °C
Installation temperature	-20 °C... + 60 °C
2002/95/EC (RoHS)	compliant

Ordering Information

Order as G_02330_HT

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Cable group X5 2 mm / 50 Ohm

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions